

2.2x4.2 Fe-Cuni Type J

Toplam Boy	Isıtılmış Boy	WATT
320	250	195
370	300	230
420	350	260
470	400	300
520	450	350
620	550	420
720	650	500
870	800	610
970	900	690
1070	1000	760
1170	1100	840



Ø	SPİRAL REZİSTANS SARIN TABLOSU												
	Sarım boyu												
	20	30	40	50	60	80	100	120	140	160	180	200	
10			195	230	230	300	350	420	500	610	690	760	
12		195	230	260	300	420	500	610	610	690	690	760	
12.5		195	230	260	300	420	500	610	610	690	690	760	
14		195	260	300	350	420	500	500	610	610	690	760	
15		195	260	300	420	500	500	610	610	610	690	760	
16		195	260	350	420	500	500	610	610	690	760	840	
18		260	300	350	420	610	610	610	690	760	840		
19		260	300	350	420	610	610	610	690	760	840		
20		300	300	420	500	610	690	760	840				
22	195	300	350	500	610	690	760	760	840				
24	195	350	420	500	610	690	760	840					
25	230	350	420	500	610	760	840						
28	230	350	420	500	610	690	840						
30	230	420	500	610	690	690	840						
32	230	420	500	610	690	760	840						
35	300	500	610	690	760	840							
38	300	500	610	690	760	840							
40	300	610	690	760	840								
50	400	690	760	840									

Standart liste dışı çap ve boylarda sarım yapılabilir.

